

Costar

MODEL
SI-M336
SI-M358
SI-M359

REMOTE HEAD
MONOCHROME CAMERA



- High resolution monochrome 1/2" Hyper HAD IT CCD sensor
- EIA: 768 (h) x 494 (v) pixels CCIR: 752 (h) x 582 (v) pixels.
- Remote head \varnothing 17mm 2m, 5m or 10m cable lengths, detachable head
- Improved dynamic range and smear performance
- Extreme sensitivity. High S/N ratio >56 dB
- Interlaced or non-interlaced scanning
- Field or frame integration mode
- Electronic shutter or asynchronous trigger shutter
- Continuous variable shutter in trigger mode 2
- Long time integration with external VD pulses
- ***flex trig***® Extensive range of customized trigger modes for OEM applications
- HD/VD synchronization input or output - 75 Ohm or TTL level
- Exposure Enable (EEN) and Write Enable (WEN) output
- Frame grabber friendly interface



Specifications for SI-M336/M358/M359

Specifications


SI-M356/M358/M359C | SI-M356/M358/M359E

TV Standard	EIA	CCIR
CCD sensor	1/2" Hyper HAD Interline transfer CCD	
Effective no. of pixel	EIA: 768(H) x 494(V) 380,000 approx.	CCIR: 752(H) x 582) 440,000 approx.
Scanning area	6.45mm (H) x 4.84mm(V)	
Scanning system	EIA: 2:1 Interface Non-interlace (1/60 sec.)	CCIR: 2:1 Interface Non-interlace (1/50 sec.)
Scanning freq.	EIA H: 15.734KHz V 59.94Hz	CCIR H: 15.625KHz V 50Hz
Sync. system	1. Ext. HD/VD Input: 4.0Vp-p +2.0V at 75Ω terminated (For TTL input 2.0V - 5.0V, set SW2 at OFF position) 2. Ext. trigger input: 4.0V +2.0Vp-p non-terminated 3. Int. HD/VD output: 4.0Vp-p at 75Ω non-terminated 4. Pixel Clock output (User option): 4.0V	
Resolution	H: 570 TV lines, V:480 TV lines (at frame accumulation mode)	H: 570 TV lines, V:480 TV lines (at frame accumulation mode)
S/N ratio	56dB or more (AGC off, Gamma = 1.0), 100KHz - 4.2MHz	
Sensitivity	500lux (F8, AGC off)	
Min. illumination on CCD sensor	0.05lux (F1.4, AGC on, Video level - 5dB)	
Normal Shutter	Off, 1/100, 1/250, 1/500, 1/1000, 1/2000, 1/4500, 1/10,000 sec.	
High Speed Shutter	1/20,000, 1/40,000, 1/60,000, 1/80,000, 1/100,000, 1/200,000, 1/400,000, 1/800,000 sec	
Ext. Trigger Shutter	Mode-1	1/60 - 1/800,000 sec.
	Mode-2	1/77 - 1/10,000 sec.
	Mode-3*	2 - 1/10,000 sec.
	Long Term Exposure	2 FLD - 120 FLD
Video Output	VS 1.0Vp-p at 75Ω terminated	
Gamma Correction	1.0 or 0.45	
Gain	Manual (GAIN VR: 0 - +15db) or AGC	
Operating temperature	-5°C to +45°C	
Humidity	20 - 80% non-condensing	
Power	12V DC ±10%, 3.6W (M336), 3.3W (M358/M359)	
Dimensions (control unit)	40 x 50 x 80 mm (HxWxD)	
Weight (control unit)	210g	
Dimensions (camera head)	ø17 x 60 mm (M336)	
Dimensions (camera head)	ø17 x 95 mm (M358/M359)	
Weight (camera head)	10 g (M336), 15 g (M358/M359)	
Lens Mount	M15.5 x 0.5	

* HD sync. VD sync./Trigger input or output by internal straps. Inputs TTL or 75 Ohm terminated by internal straps.

Connection Description

DC-IN/SYNC.



- Pin 1 Ground
- 2 +12V DC
- 3 Ground
- 4 Video output
- 5 Ground
- 6 HD in/HD out
- 7 VD in/VD out
- 8 Ground
- 9 N.C. Y/Pixel clock out
- 10 Ground
- 11 +12V DC
- 12 Ground


TRIGGER




- Pin 1 N.C.
- 2 EEN output
- 3 Ground
- 4 N.C.
- 5 Trig. input
- 6 WEN pulse output

Dimensions


Front view




Side view




Bottom view



Top view




Switch Setting




SW1-1 ED2	SW1-2 ED1	SW1-3 ED0	Shutter speed (sec.)	
			Elect. Shutter	Ext. trigger shutter
OFF	OFF	OFF	1/80	1/20,000
OFF	OFF	ON	1/100	1/40,000
OFF	ON	OFF	1/250	1/60,000
OFF	ON	ON	1/500	1/80,000
ON	OFF	OFF	1/1000	1/100,000
ON	OFF	ON	1/2000	1/200,000
ON	ON	OFF	1/4500	1/400,000
ON	ON	ON	1/10,000	1/800,000

Normal Speed High Speed



Camera Head Dimensions

SI-M336/M358/M359



Ordering Information

SI-M336 1/2" Monochrome Remote Head Camera CCIR/EIA 2 m Cable
 SI-M358 1/2" Monochrome Remote Head Camera CCIR/EIA 5 m Cable
 SI-M359 1/2" Monochrome Remote Head Camera CCIR/EIA 10 m Cable
 OP 735 Special Lens 7.5 mm



3744 Industry Ave., Ste. 402
 Lakewood, CA 90712
 Toll Free (888) 446-1301
 Local (562) 424-9093
 Fax (562) 424-9203

URL: www.costar-usa.com
 Email: CHUCKM@COSTAR-USA.COM